

Access Self Contained Vacuum Loaders

AL2 and AL5

Features:

Self-contained vacuum motor loaders are shipped complete, ready to install and use. All standard unit base prices include: Stainless Steel Cylindrical Body Angled Toward User for Easy Access; Cast Aluminum Base with Integral Discharge Pan, Protective Stand-offs and Terminal Box; Hinged Lid (removable) with Captive Draw Latches; No-tools Filter Servicing of Drop-in Disc Filter; Filter Blowback; Bolt-on Replaceable Inlet/Outlets; 1.75" Vertical Feed Tube and Flex Hose with Clamps; long life, powerful vacuum motors, and a choice of 2 sizes; the AL5 and the AL2.

Options include a direct feed configuration with a choice of viewing chamber sizes, ratio loading and stainless steel material contact points and many more. Blowback may be deleted if not required for conveying clean, virgin pellets and/or low throughputs. Blowback is required for ratio loading.

Base options that may be changed include: Gravity Discharge with Integral Reed Demand Switch, Time Fill Operation (Demand Sensor Only), Single Tube (One Material) Loading, choice of 110 VAC or 220 VAC Operation, and optional line sizes (1.5 inch OD for AL2, and 2 inch for AL5)

Model AL2 has a 5/8 HP vacuum motor and 0.2 cuft volume capacity and IT06 compatible flange mount arrangement.

Model AL5 has a 7/8 HP vacuum motor, and may be equipped with the new brushless motor option in place of the standard 4 brush motor. The AL5 has 0.5 cuft volume capacity and IT07 compatible flange mount arrangement.

All Loaders include the ELC-M control and the optional ControlMate pendant allows operators to control more advanced loading features such as blowback pulses, dump time, purge time, ratio time, and ratio layers. ControlMate is attached to each ELC-M control by means of a removable, shielded CAT5 ethernet cable. A single ControlMate pendant can be used on multiple ELC-M controls by having the operator carry ControlMate from one ELC-M to the next to adjust load parameters.

Base Packages:

	MODEL AL2		MODEL AL5			
	AA	AB	AA	AB	AC	AD
	\$2,439	\$3,325	\$2,960	\$3,846	\$3,388	\$4,274
Single Tube 1.75" OD Inlet	X		X		X	
Ratio Valve with Dual 1.75" OD Inlets		X		X		X
5/8 hp integral motor	X	X				
7/8 hp integral motor			X	X		
1.3 hp brushless integral motor					X	X

Feature Selections

PRICE ADDER:

Line Size

1.5" OD	\$54
1.75" OD	n/c
2" OD	\$54

Voltage

220 Volt Operation - AL2	\$94
220 Volt Operation - AL5 (Brushless Motor not available in 220V)	\$134
UL Labeled (N/A - Consult Product Manager)	

Pre-engineered Options (add prices - shipped with receiver)

PRICE ADDER:

ControlMate Pendant (includes 10' or 15' ethernet patch cable)	\$314
ControlMate Storage Cradle	\$70
Volume Fill Sensor	\$310
Remote Prox Sensor	
3 feet direct feed hopper fill (n.c.)	\$310
6 feet bin/drying hopper fill (n.c.)	\$310
30 feet grinder evacuation (n.o.)	\$431
6 feet cable extension	\$126
Left Side Material Inlet (9 o'clock)	n/c
(AR2 or AR5 - Blender Bin Mount typ.)	
High Wear Kit	\$174
(AR5 only - includes high wear inlet deflector.)	

Accessories (add prices - sold and shipped separately from receiver)

PRICE ADDER:

Direct Feed Glass Hopper

3 lb glass (For use with AL2 model only - sensor bracket included)	\$1,246
11 lb glass (For use with AL2 model only - sensor bracket included)	\$1,692
21 lb glass (For use with AL2 model only - sensor bracket included)	\$1,924

Direct Feed SS Hopper

10 lb. bin (For use with AL2 model only - drain port, sensor bracket n/a)	\$848
20 lb. bin (For use with AL5 model only - integral drain port, sensor bracket included)	\$1,128
40 lb. bin (For use with AL5 model only - integral drain port, sensor bracket included)	\$1,254